

The IR Video range of products provides the video surveillance technology for Inner Range's Unified Video, Access and Security solutions. The complete range of products include Video Gateways for providing the link to Inner Range's IR Connect cloud services and through to the full connected eco-system of Inner Range solutions, Edge Cameras incorporating onboard storage and video analytics, and Active Deterrence Cameras providing Video Analytic driven alarm conditions into the IR Eco-system.

The IR CONNECT Mobile Application provides users with the ability to remotely connect, arm & disarm the unified solution, receive events and alarm notifications and associated video to verify the situation on site. This comprehensive security solution incorporating Video, Access Control and Intruder Alarm protects your premises, your assets and most importantly... your people.


## Key Features

- 1/1.8" progressive scan CMOS
- Max. 8MP(3840×2160) @25/30fps resolution
- 2.8mm/4mm fixed lens optional
- Support face, human, vehicle detection and capture
- Intelligent analysis: intrusion, single line crossing, double line crossing, loitering, wrong-way, people counting and video metadata
- True WDR, 3D DNR, ROI, Defog, HLC
- 1/1 audio input/output, 1/1 alarm input/output
- Built-in SD card slot
- Smart IR distance up to 15m
- IP67, IK10



**IR-V-C8D-110**

## Dimensions (mm)



## Accessories





## Specification

Camera		
Image Sensor	1/1.8" Progressive Scan CMOS	
Max Resolution	8MP, 3840(H) × 2160(V)	
Electronic Shutter	Auto/Manual, 1/5 to 1/20,000s	
Min. Illumination	Color: 0.005 Lux @ (F1.6, AGC ON) , B/W: 0 Lux with IR	
Day & Night	Auto (ICR)	
Angle Adjustment	Pan: ±45°, Tilt: 0° to 72°, Rotation: 0° to 360°	
Lens Type		
Lens Type	Fixed focus	
Iris	Fixed iris	
Focal Length	2.8mm	4mm
F Number	F1.6	F1.6
Angle of View	H: 106°, V: 58.6°	H: 90.3°, V: 48.1°
Illuminator		
Illuminator Type	IR	
Illumination Distance	Up to 15 m (49.2 ft)	
Illumination On/Off Control	Auto/Manual	
Video		
Streaming Capability	3 Streams	
Stream/Frame Rate	Stream1: 3840×2160, 2592×1944, 2560×1520, 2560×1440, 2304×1296, 1920×1080, 1280×720 @25/30fps Stream2: D1, VGA, CIF @25/30fps Stream3: VGA, CIF, QVGA @25/30fps	
Bit Rate Control	CBR/VBR	
Bit Rate	Stream1: 200 Kbps to 16 Mbps Stream2: 100 Kbps to 6 Mbps Stream3: 100 Kbps to 3 Mbps	
Smart Encoder	Support	
Region of Interest (ROI)	Off/On (8 Zone, Rectangle)	
Audio		
Compression	G.711, RAW_PCM	
Bit Rate	64Kbps (G.711), 128Kps (RAW_PCM)	
Smart Function		
Multi-Object Detection	Supports face, human, vehicle detection and capture	
Intelligent Analysis	Intrusion, Single line crossing, Double line crossing, Loitering, Wrong-way Support alarm triggering by specified target types (human and vehicle).	
People Counting	Support	

Image	
Image Adjustment	Brightness, Sharpness, Contrast, Saturation adjustable
Aisle Mode	Support
Mirror	Support
White Balance	Auto/Manual
Day/Night Setting	Auto, Day, Night, Time
Noise Reduction	2D/3D DNR
Image Enhancment	HLC, BLC, Defog
Wide Dynamic Range	True WDR
S/N Ratio	55dB
Privacy Masking	Support
Smart Function	
Multi-Object Detection	Supports face, human, vehicle detection and capture
Intelligent Analysis	Intrusion, Single line crossing, Double line crossing, Loitering, Wrong-way Support alarm triggering by specified target types (human and vehicle).
People Counting	Support
Network	
Protocols	IPv4/IPv6, HTTP, HTTPS, TCP/UDP, RTSP/RTCP/RTP, DHCP, DNS, DDNS, PPPoE, SMTP, 802.1x, UPnP, FTP, NTP, ARP, SNMP, TLS/SSL
Interoperability	ONVIF, SDK
Streaming Method	Multicast
Max. User Access	10 Users
Web Viewer	<IE11, Chrome, Firefox
Language	English, Chinese, Polish, Italian, Portuguese, Spanish, Russian, French, Czech, Hungarian. Default: English
Interface	
Network Interface	1 Ethernet (10/100 Base-T) RJ-45 Connector
Built-in Microphone	Support
Audio Interface	1ch Input, 1ch Output
Alarm Interface	1ch Input, 1ch Output
SD Card Slot	Built-in, up to 512GB
Reset Button	Support
Electrical	
Power Supply	DC12V (-15% to +25%)/PoE (IEEE 802.3af)
Power Communication	Max. 5.5 W
Operating Temperature	-35°C to 60°C (-31°F to 140°F )
Operating Humidity	Less than 90% RH
Ingress Protection	IP67, IK10
Certifications	CE/FCC
Casing	Metal
Dimensions	99.6 × 99.6 × 63.3 mm (3.92 × 3.92 × 2.49 inch)
Net Weight	0.48 kg (1.06 lb)